

FF5025-DDATACXX 系列  
双光口 25G 以太网适配器  
用户手册

北京网迅科技有限公司

---





---

### 1.1.3

- IPv4 TCP RSC
- FCOE
- 256 KB
- IP/TCP/UDP/STCP
- UDP
- CRC
- VLAN
- MAC/VLAN
- 

### 1.1.4

- PCIe Gen4x8
- MSI/MSI-X
- A/B/C/D PCIe Completion Timeout Range
- 
- TCP
- PCIe TPH/FLR/ID0/ARI/VPD/ECRC
- 256B (MPS)/1KB (MRRS)
- PCIe
- D0 D3 ACPI 28E616312CB4}T#TQ EMC /P 696B 0 1 166.7 500.7 Tm0 G[-]T#TQSI



(A)	0.424	0.448	0.610
W	5.1	5.4	7.3

*Note: Typical conditions: T<sub>j</sub>=55°C, normal voltages, and no traffic.*

**2 Idle**

1.2.3


---

## 1.2.6 PCB

2.54um      0.8um  
2.54um      0.5um

## 1.2.7

<b>Manufacturer</b>	<b>Part Number</b>	<b>Module Type</b>
FIBERTOP	SFP28-25GSR-HYT	25G
WTD	RTXM330-551	25G
Hi sense	LTF8505-BC+	25G
Intel Corp	LTF8505-BC-IN	25G
FIBERTOP	SFP28-25GSRD-HYT	25G
HUAWEI	LTF8501-BC+	10G
SONT	XP-8G10-01	10G
AVAGO	AFBR-709SMZ	10G
WTD	RTXM228-551	10G
Fi ni sar	FTLX8571D3BCL	10G

5

## 2

### 2.1

- FF5025-DDATACXX      25G
- 
- 
- 
- 
- 1

### 2.2

-



- 
- - 
  - 
  - 
  - 
  - 
  -

PCIe X8 X16

## 2.4 驱动程序安装

25G

### 3

#### 3.1

MTBF( )	1000000	

### 4

#### 4.1 光模块插入后 Link 指示灯不亮

- 
- 
- 
- 
- 
- 

PCIe

Link

---

## 4.2 光纤线连接后 ACT 指示灯不闪烁

➤ TX RX

➤

➤

➤

## 5

➤

➤

➤

➤

➤

➤

➤

➤

0° C — 55° C

0% — 90%